

Model Number

PFX-5526 Low Profile All LED Exit & Emergency Combo



Project:	
Type:	
Catalog #:	

STANDARD



OPTIONAL

ILLUMINATION

- Adjustable long lasting, efficient ultra bright white LED lamp heads.
- One, 0.5W white LED per lamp head.
- Unique all inclusive lamp, reflector and lens assembly.
- Long-lasting, energy efficient Red or Green LED EXIT sign illumination.

ELECTRICAL

- Dual 120V/277 voltage standard. Optional dual 120V/230V available.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- 3.6V long life, maintenance-free, rechargeable Ni-Cd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- EZ-snap thermoplastic mounting canopy included – provides top or end mount.
- Universal K/O pattern on back plate for wall mount.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact, thermoplastic in white or black finish.


OPTIONS

- SPV: UL Listed for special voltage option.
- HL: Provides increased center-to-center spacing (2.0W per head).
- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes. Universal 120-277 voltage.
- RC: Remote capacity of up to 1.0 watts.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- UL Listed for damp locations (0°C – 40°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Certified to CEC under Title 20 Regulations.

DIMENSIONS



ORDERING INFORMATION

Sample Part Number: **PFX5526CEU3RW**

NOTES:

¹ -HL and -RC options cannot be combined. 0.5W of remote capacity available standard with -HL option

MODEL	No. of FACES	LETTER COLOR	HOUSING COLOR	OPTIONS
PFX5526 CEU	3 Universal Single/Double Face	R Red G Green	W White B Black	RC Remote Capacity ¹ HL High Lumen LED ¹ SDT Self-Diagnostics SPV 120/230 Volt 50/60Hz

PFX-5526 Low Profile All LED Exit & Emergency Combo

Project:	
Type:	
Catalog #:	

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)			INPUT AMPS (A)		
	120V	230V	277V	120V	230V	277V
PFX5526CEU RED	1.4	1.2	1.7	0.08	0.09	0.09
PFX5526CEU RED RC/HL	1.6	1.6	1.6	0.12	0.11	0.11
PFX5526CEU GREEN	1.1	1.2	1.3	0.08	0.09	0.09
PFX5526CEU GREEN RC/HL	1.6	1.6	1.6	0.12	0.11	0.11
PFX5526CEU RED SDT	2.5	-	2.5	0.05	-	0.05
PFX5526CEU RED RC-SDT/HL	3.0	-	3.0	0.05	-	0.05
PFX5526CEU GRN/RC-SDT/HL	2.7	-	2.7	0.05	-	0.05

REMOTE LAMP COMPATIBILITY

MODEL NUMBER	BATTERY	REMOTE CAPACITY	COMPATIBLE REMOTE HEAD FAMILY													
			RHLED	MRHLED	RH16LED	RH16		RH		RHR		SRH		SRHLED		
			MV			6V	12V	6V	12V	6V	12V	6V	12V			
PFX5526CEU-RC	3.6V	1W	x	x												
PFX5526CEU-HL	3.6V	0.5W		x												