




PFX-8500

Model: 8500L52MWH/8500L60MWH
8500L52MBK/8500L60MBK
8500L52BNSLV/8500L60BNSLV



Brushed Nickel/Silver



Matte Black



Matte White



Key Features & Benefits

- ABS Blades with Solid Finishes and Sleek Minimalist Design
- DC Motor and ETL listed
- Lifetime motor warranty



SOFT WHITE (3000K)

BRIGHT WHITE (4000K)

DAYLIGHT (5000K)

Adjust color of light with included remote control

Product Specifications

Fan Size in Inches 52"/ Downrod mount only, Flat or Angled ceiling (max. 18 degree) 60"/ Downrod mount only, Flat or Angled ceiling (max. 18 degree)	CFM (High) 5663 6100	Motor Type (AC, DC)/Size DC / 156x8 DC / 156x12	Indoor/Outdoor/Finish Indoor Only
Lead Wire 12" standard coming from motor with quick connector. Additional 44" extension lead wires with quick connectors included to allow for a 48" downrod (sold separately)	Blade Arms N/A	Damp or Wet Rated Dry Rated	Reversible, Blade Finish Non-Reversible Available in Matte Black / Matte White or Silver Finish
No. of Blades/Blade Material 3/ABS	Remote Control (Y/N) Y	Distance from ceiling to bottom of the light kit once installed: 12.72"	Distance from Ceiling to bottom of blade once installed: 11.08"
Light Kit (Y/N) Y / (must be installed with Light kit)	Lens Type PC	Type of Bulbs LED Module (can be replaced)	Bulb Wattage 18W (Dimmable)

For LED Only

Lumen Output (Raw/Fixture) 1314/1000	Lumens/Watt 56	Color Temperature / CRI 3000K/4000K/5000K/≥90	LED Chip Brand BRIDGELUX	Driver Module AC
---	-------------------	--	-----------------------------	---------------------

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.