

**CV203** LED CANOPY LUMINAIRE

PROJECT NOTES DATE









REV: 06 2021

TYPE



## **COMPACT, HEAVY-DUTY HOUSING**

The CV203 is a 9" Square Canopy Luminaire with a Die Cast Aluminum Body and Prismatic Polycarbonate Diffuser with UV

## WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

## **EASY TO INSTALL MOUNTING**

The CV203 can be Directly Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry

**120-277V STANDARD TYPE VS DISTRIBUTION OPERATING TEMPERATURE -20C TO 40C PRODUCT APPLICATIONS** 

**Building Canopy** Storage Facilities Parking Garages **Gas Stations** 

Tunnels

When Specifying Options, Please Check with Factory for Availability and Lead-Time. Any finish other than Paraflex bronze order is non-cancelable and non-returnable. Any modified product, any selected options added to standard products, deem order non-cancelable and non-returnable. All RMA, Return Material Authorization, must be factory approved

# **ORDERING GUIDE** WATTAGE

#### **COLOR TEMPERATURE (CCT)** HOUSING COLOR

## **OPTIONS & ACCESSORIES**

Sample Part # CV203 - 12W - 35K - BZ - PC1 - D1

MODEL CV203

> **12W** 12 WATTS 27K 2700K - WARM WHITE 24W 24 WATTS 30K 3000K - WARM WHITE

**36W** 36 WATTS 35K 3500K - NEUTRAL WHITE

40K 4000K - NEUTRAL WHITE 50K 5000K - COOL WHITE

57K 5700K - DAYLIGHT

**BZ** BRONZE (STANDARD) **WH** WHITE

**BL** BLACK **SL** SILVER

**CC** CUSTOM COLOR

MS MOTION SENSOR

MS-D2 motion sensor with bilevel dimming

D1 0-10V DIMMING


D2 STEP DIMMING (120V ONLY)


V1\* 480/347V INPUT (120-277V STANDARD) \*NOT AVAILABLE WITH A MOTION SENSOR

## PRODUCT SPECIFICATIONS

| NOMINAL WATTAGE | SYSTEM WATTAGE | CCT   | LUMEN   | EFFICACY |
|-----------------|----------------|-------|---------|----------|
| 12W             | 12.65          | 3000K | 1432.50 | 113.24   |
| 12W             | 12.65          | 4000K | 1475.48 | 116.64   |
| 12W             | 12.65          | 5000K | 1519.74 | 120.14   |
| 24W             | 23.54          | 3000K | 2865.00 | 121.71   |
| 24W             | 23.54          | 4000K | 2950.95 | 125.36   |
| 24W             | 23.54          | 5000K | 3039.48 | 129.12   |
| 36W             | 34.27          | 3000K | 4405.69 | 128.56   |
| 36W             | 34.27          | 4000K | 4537.86 | 132.41   |
| 36W             | 34.27          | 5000K | 4674.00 | 136.39   |

### PRODUCT DIMENSIONS





**POWFR** 

POWER FACTOR > 0.90 - THD < 20

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

