

Project:	
Type:	
Catalog #:	

STANDARD



OPTIONAL



ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LED.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 1.2V Long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- Aesthetically pleasing, curved face, rounded corner design.
- EZ snap-out chevron directional indicators.


OPTIONS

- **SDT:** Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes. Universal 120-277 voltage.
- **Custom:** Signs available with requested 'special' wording.
- **USA:** Substantial transformation assembly in the U.S. complies with "Assembled in USA" under the Buy American Act.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.

DIMENSIONS



ORDERING INFORMATION

Sample Part Number: **PFX5504EZRXTU2RWEM**

	MODEL	No. of FACES	LETTER COLOR	HOUSING COLOR	BATTERY	BATTERY
SALIDA face plate option available. Check with Factory.	PFX5504	2	R Red	W White	(blank) AC Only	SDT Self-Diagnostics ^{2,3}
	EZRXTU		G Green	B Black	EM	Custom Custom wording
			RG Red/Green ¹			USA Assembled in USA

¹ Field selectable

² Available only with EM units.

³ Not available with RG units.

PFX-5504 Compact Thermoplastic Exit Sign

Project:	
Type:	
Catalog #:	

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
PFX5504EZRXTU-RED/GREEN EM	1.0	1.0	0.1	0.1
PFX5504EZRXTU-RED SDT	2.5	2.5	0.05	0.05
PFX5504EZRXTU-GREEN SDT	2.7	2.7	0.05	0.05