

CL390

LED CANOPY LUMINAIRE



PROJECT
NOTES

DATE

TYPE

REV: 03 2020



HEAVY-DUTY, 360° ADJUSTABLE HOUSING

Die Cast Aluminum Housing with Durable, Dark Bronze Powder Coat Finish, and Polycarbonate Lens

IP-65 RATED WET LOCATION RATED

Engineered and Constructed for Exterior Environments

MOUNTING PLATE

The CL390 Includes a Mounting Plate for Easy Mounting Over a Junction Box

120-277V STANDARD & 0-10V DIMMING STANDARD

PRODUCT APPLICATIONS

- | | |
|----------------|------------|
| Parking Garage | Bridges |
| Walkways | Catwalks |
| Tunnels | Stairwells |
| Storage Areas | |

When Specifying Options, Please Check with Factory for Availability and Lead-Time.

ORDERING GUIDE

Sample Part # CL390 - 45W - 50K - BZ - PC

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
CL390	45W 45 WATTS 80W 80 WATTS	50K 5000K - COOL WHITE	BZ BRONZE (STANDARD)	PC 120V-277V PENCIL TYPE PHOTOCELL

PRODUCT SPECIFICATIONS

WATTAGE	CCT	DELIVERED LUMENS	EFFICACY	CRI
45W	5000K	4,948 LM	112 LM/W	>80
80W	5000K	9,548 LM	120 LM/W	>80

HOUSING CONSTRUCTION

Heavy Duty Die Cast Aluminum Housing Gasketed to Provide IP65 rating when Paired with Lens

LENS CONSTRUCTION

Durable UV- and Heat Resistant Polycarbonate

DIMENSIONS

45W: 10"x10"x4" & 80W: 14"x14"x4"

FINISH

High Quality Dark Bronze Powder Coat Rated for Outdoor Locations

VOLTAGE

120-277V Input Standard. THD <20% Power Factor >90%

CERTIFICATIONS

cULus conforms to UL 1598 and 8750 conforms to CSA 22.2 & DLC Standard Listed. Complies with FCC (Part 15, Class B). Complies with EN61000-4-5, surge immunity test (1kV).

OPERATING TEMPERATURE

Wet Location Listed. Suitable for -40C to 40C ambient temperatures

LUMEN MAINTENANCE

L70 rating of over 60,000 hours

WARRANTY

Standard 5-Year Warranty