

CV15G
LED CANOPY LUMINAIRE



PROJECT
NOTES

DATE

TYPE

REV: 18 1025



COMPACT, HEAVY-DUTY HOUSING

The CV15G is a 15" Circular Canopy Luminaire with a Die Cast Aluminum Body and Prismatic Polycarbonate Diffuser with UV Inhibitors

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The CV15G can be Directly Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry

120-277V STANDARD TYPE VS DISTRIBUTION

OPERATING TEMPERATURE -20C TO 40C

PRODUCT APPLICATIONS

- Building Canopy
- Parking Garages
- Tunnels
- Storage Facilities
- Gas Stations

When Specifying Options, Please Check with Factory for Availability and Lead-Time.


ORDERING GUIDE Sample Part # CV15G - 12W - 30K - BZ - PC1

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
CV15G			BZ	
	12W	30K 3000K - WARM WHITE	BZ BRONZE	MS MOTION SENSOR*
	24W	40K 4000K - NEUTRAL WHITE		D1 0-10V DIMMING
	36W	50K 5000K - COOL WHITE		EM EMERGENCY BATTERY PACK*
	48W			*CONSULT FACTORY FOR ESTIMATED SHIP DATE
	60W			
	72W*	QUANTITY	SHIPS	
	84W*	1-5 Pieces (Before 11AM EST)	Same Day	
	96W*	5-25 Pieces	3 Days	
		25-100 Pieces	1 Week	

PRODUCT SPECIFICATIONS

NOMINAL WATTAGE	SYSTEM WATTAGE	CCT	LUMENS	EFFICACY
12W	12.65	3000K	1362.50	107.71
12W	12.65	4000K	1403.38	110.94
12W	12.65	5000K	1445.48	114.27
24W	23.54	3000K	2725.00	115.76
24W	23.54	4000K	2806.75	119.23
24W	23.54	5000K	2890.95	122.81
36W	34.27	3000K	4097.74	119.57
36W	34.27	4000K	4220.68	123.16
36W	34.27	5000K	4347.30	126.85
48W	46.6	3000K	5450.00	116.95
48W	46.6	4000K	5613.50	120.46
48W	46.6	5000K	5781.91	124.08
60W	56.83	3000K	6812.50	119.88
60W	56.83	4000K	7016.88	123.47
60W	56.83	5000K	7227.38	127.18
72W	67.26	3000K	8175.00	121.54
72W	67.26	4000K	8420.25	125.19
72W	67.26	5000K	8672.86	128.95
84W	81.55	3000K	9537.50	116.95
84W	81.55	4000K	9823.63	120.46
84W	81.55	5000K	10118.33	124.08
96W	92.21	3000K	10900.00	118.21
96W	92.21	4000K	11227.00	121.75
96W	92.21	5000K	11563.81	125.41

PRODUCT DIMENSIONS



POWER

POWER FACTOR >90 - THD <20

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.