

CV203

LED CANOPY LUMINAIRE



PROJECT

DATE

TYPE

NOTES

REV: 18 1025



QUICK SHIP

COMPACT, HEAVY-DUTY HOUSING

The CV203 is a 9" Square Canopy Luminaire with a Die Cast Aluminum Body and Prismatic Polycarbonate Diffuser with UV Inhibitors

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The CV203 can be Directly Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry

120-277V STANDARD TYPE VS DISTRIBUTION

OPERATING TEMPERATURE -20C TO 40C

PRODUCT APPLICATIONS

- Building Canopy
- Storage Facilities
- Parking Garages
- Gas Stations
- Tunnels

When Specifying Options, Please Check with Factory for Availability and Lead-Time.

ORDERING GUIDE

Sample Part # CV203 - 12W - 30K - BZ - D1


MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
CV203			BZ	D1
	12W	30K 3000K - WARM WHITE	BZ BRONZE	D1 0-10V DIMMING
	24W	40K 4000K - NEUTRAL WHITE		
	36W	50K 5000K - COOL WHITE		

QUANTITY	SHIPS
1-5 Pieces (Before 11AM EST)	Same Day
5-25 Pieces	3 Days
25-100 Pieces	1 Week

PRODUCT SPECIFICATIONS

NOMINAL WATTAGE	SYSTEM WATTAGE	CCT	LUMENS	EFFICACY
12W	12.65	3000K	1432.50	113.24
12W	12.65	4000K	1475.48	116.64
12W	12.65	5000K	1519.74	120.14
24W	23.54	3000K	2865.00	121.71
24W	23.54	4000K	2950.95	125.36
24W	23.54	5000K	3039.48	129.12
36W	34.27	3000K	4405.69	128.56
36W	34.27	4000K	4537.86	132.41
36W	34.27	5000K	4674.00	136.39

PRODUCT DIMENSIONS



POWER

POWER FACTOR >90 - THD <20

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.