

CV304

LED CANOPY LUMINAIRE



PROJECT

DATE

TYPE

NOTES

REV: 18 1025



QUICK SHIP

When Specifying Options, Please Check with Factory for Availability and Lead-Time.

COMPACT, HEAVY-DUTY HOUSING

The CV304 is a 12" Square Canopy Luminaire with a Die Cast Aluminum Body and Prismatic Polycarbonate Diffuser with UV Inhibitors

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The CV304 can be Directly Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry

120-277V STANDARD

TYPE VS DISTRIBUTION

PRODUCT APPLICATIONS

- Building Canopy
- Storage Facilities
- Parking Garages
- Gas Stations
- Tunnels

ORDERING GUIDE


Sample Part # CV304 - 12W - 30K - BZ - PC1

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
CV304			BZ	
	24W	30K 3000K - WARM WHITE	BZ BRONZE	PC1 120V PHOTOCELL
	36W	40K 4000K - NEUTRAL WHITE		PC2 208/277V PHOTOCELL
	48W	50K 5000K - COOL WHITE		MS MOTION SENSOR*
	60W			D1 0-10V DIMMING
	72W*			EM EMERGENCY BATTERY PACK*
		QUANTITY	SHIPS	*CONSULT FACTORY FOR ESTIMATED SHIP DATE
		1-5 Pieces (Before 11AM EST)	Same Day	
		5-25 Pieces	3 Days	
		25-100 Pieces	1 Week	

PRODUCT SPECIFICATIONS

NOMINAL WATTAGE	SYSTEM WATTAGE	CCT	LUMENS	EFFICACY	DLC LISTING
24W	23.54	3000K	2,875.45	122.15	PREMIUM
24W	23.54	4000K	2,961.71	125.82	PREMIUM
24W	23.54	5000K	3,050.57	129.59	PREMIUM
36W	34.27	3000K	4,186.14	122.15	PREMIUM
36W	34.27	4000K	4,311.72	125.82	PREMIUM
36W	34.27	5000K	4,441.07	129.59	PREMIUM
48W	46.60	3000K	5,692.27	122.15	PREMIUM
48W	46.60	4000K	5,863.04	125.82	PREMIUM
48W	46.60	5000K	6,038.93	129.59	PREMIUM
60W	56.83	3000K	6,941.88	122.15	PREMIUM
60W	56.83	4000K	7,150.14	125.82	PREMIUM
60W	56.83	5000K	7,364.64	129.59	PREMIUM
72W	67.26	3000K	8,215.92	122.15	PREMIUM
72W	67.26	4000K	8,462.40	125.82	PREMIUM
72W	67.26	5000K	8,716.27	129.59	PREMIUM

PRODUCT DIMENSIONS



POWER

POWER FACTOR >90 - THD <20

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.