

FLEXLED
DC200-90

LARGE 90° CUT-OFF LED WALLPACK



5 YEAR STANDARD WARRANTY | RATED LIFE: 85,000 HOURS+

HOUSING:

Die Cast Aluminum with Bronze Powder Coat and Heat and Impact Resistant Glass

CERTIFICATIONS:

Conforms to UL Standards UL-8750 and UL-1598. ETL Listed for USA and Canada. Certified to CSA22.2

MOUNTING:

Direct over 4" outlet box or surface wired through 1/2" conduit entries.

ENVIRONMENT:

Outdoor/Wet Location
IP65 Rated

DRIVER:

Constant Current Class 2 100-277 VAC 50/60Hz
Power Factor: >0.98

ARRA COMPLIANT:

Buy American Compliant under Section 1605 of the American Re-Investment and Recovery Act.

ORDERING GUIDE

STANDARD CONFIGURATION: DC200L90.56W.40K

| MODEL | WATTS | COLOR TEMPERATURE (CCT) | ACCESSORIES |
|----------|-------|---------------------------|---|
| DC200L90 | 28W | 30K 3000K - Warm White | DIM Accessory - 0-10V Dimmable Driver |
| | 42W | 40K 4000K - Neutral White | R300755 Accessory - 120V Photocell |
| | 56W | 50K 5000K - Cool White | R300756 Accessory - 208V/277V Photocell |
| | 70W | 55K 5500K - Daylight | |
| | 84W | | |

| WATTS | DELIVERED LUMENS | EFFICACY | CRI | ~HID |
|-------|------------------|----------|-----|------|
| 28W | 2,660lm | 110 lm/W | >85 | 175W |
| 42W | 4,210lm | 110 lm/W | >85 | 250W |
| 56W | 5,440lm | 115 lm/W | >85 | 400W |
| 70W | 6,710lm | 115 lm/W | >85 | 400W |
| 84W | 8,140lm | 115 lm/W | | 400W |

DIMENSIONS

