













5 YEAR STANDARD WARRANTY | RATED LIFE: 85,000 HOURS+

HOUSING:

Die Cast Aluminum with Bronze Powder Coat and Heat And Impact Resistant Glass

MOUNTING:

MOUNTING BRACKET SOLD SEPERATELY. Optional Trunnion, Slip-Fitter, Swivel or Straight Arm.

DRIVER:

Constant Current Class 2 100-277 VAC 50/60Hz Power Factor: >0.98

CERTIFICATIONS:

Conforms to UL Standards UL-8750 and UL-1598. ETL Listed for USA and Canada. Certified to CSA22.2

ENVIRONMENT:

Outdoor/Wet Location IP65 Rated

ARRA COMPLIANT:

Buy American Compliant under Section 1605 of the American Re-Investment and Recovery Act.

ORDERING GUIDE


STANDARD CONFIGURATION: DC400.42W.40K

MODEL	WATTS	COLOR TEMPERATURE (CCT)		ACCESSORIES		
DC400	28W	30K	3000K - Warm White	DIM	Accessory - 0-10V Dimmable Driver	
	42W	40K	4000K - Neutral White	R300755	Accessory - 120V Photocell	
	56W	50K	5000K - Cool White	R300756	Accessory - 208V/277V Photocell	
	70W	55K	5500K - Daylight	R300664	Accessory - Trunnion Bracket	
				R300684	Accessory - Heavy Duty Swivel	
				R392098	Accessory - 6" Straight Arm	

SPECIFICATIONS

WATTS	DELIVERED LUMENS	EFFICACY	CRI	~HID
28W	2,660lm	110 lm/W	>85	175W
42W	4,210lm	110 lm/W	>85	250W
56W	5,440lm	115 lm/W	>85	400W
70W	6,710lm	115 lm/W	>85	400W

DIMENSIONS



Specifications subject to change without notice.