













5 YEAR STANDARD WARRANTY | RATED LIFE: 85,000 HOURS+

#### **HOUSING:**

Die Cast Aluminum with Bronze Powder Coat and Heat and Impact Resistant Glass

#### **MOUNTING:**

Direct over 4" outlet box.

#### **DRIVER:**

Constant Current Class 2 100-277 VAC 50/60Hz Power Factor: >0.98

#### **CERTIFICATIONS:**

Conforms to UL Standards UL-8750 and UL-1598. ETL Listed for USA and Canada. Certified to CSA22.2

#### **ENVIRONMENT:**

Outdoor/Wet Location IP65 Rated

### ARRA COMPLIANT:

Buy American Compliant under Section 1605 of the American Re-Investment and Recovery Act.

## **ORDERING GUIDE**

STANDARD CONFIGURATION: DCST.28W.40K

MODEL	.	WATTS	COLOR TEMPERATURE (CCT)		ACCESSORIES	
DCST		14W	30K	3000K - Warm White	DIM	Accessory - 0-10V Dimmable Driver
		28W	40K	4000K - Neutral White		
	.	42W	50K	5000K - Cool White		
		56W	55K	5500K - Daylight		

## **SPECIFICATIONS**

WATTS	DELIVERED LUMENS	EFFICACY	CRI	~HID
14W	1,380lm	110 lm/W	>85	100W
28W	2,660lm	110 lm/W	>85	175W
42W	4210lm	115 lm/W	>85	250W
56W	5,440lm	115 lm/W	>85	400W

# Specifications subject to change without notice.

# **DIMENSIONS**

