

ZLED
ZSLM
 LED LOW-PROFILE WALLPACK



5 YEAR STANDARD WARRANTY
 RATED LIFE: 50,000 HOURS+



HOUSING:

Die Cast Aluminum with Silver Powder Coat with Heat and Impact Resistant Glass

DRIVER:

Dimmable drivers, photocells 120-277 VAC 50/60Hz
 Power Factor: >0.98

MOUNTING:

90° Adjustable of beam angle with full cut off option

ENVIRONMENT:

Outdoor/Wet Location. IP66 Rated

CERTIFICATIONS:

UL Listed for USA and Canada.
 Conforms to UL-8750 and UL-1598. Certified to CSA22.2



ORDERING GUIDE & SPECS

HANDS FREE MOUNTING BRACKET AND EASY INSTALLATION

PART NUMBER	WATTS	LUMENS	EFFICACY	COLOR TEMPERATURE	CRI
ZSLM.13W.50K*	13W	1,650lm	118 lm/W	5000K	>70
ZSLM.18W.50K*	18W	2,190lm	109 lm/W	5000K	>70
ZSLM.26W.50K*	26W	2,900lm	97 lm/W	5000K	>70
ZSLM.40W.50K*	40W	4,455lm	111 lm/W	5000K	>70
ZSLM.52W.50K*	52W	5,658lm	109 lm/W	5000K	>70
ZSLM.80W.50K*	80W	7,280lm	96 lm/W	5000K	>70
ZSLM.104W.50K*	104W	10,660lm	102.5 lm/W	5000K	>70
ZSLM.114W.50K*	114W	10,951lm	96 lm/W	5000K	>70

Specifications subject to change without notice. * Indicates DLC Qualified Product