


PFX-3306

OUTDOOR BOLLARD TOP FIXTURE



Call For Custom Length Stub
Posts & Pier Mount Adapters

PFX-3306 Lighting's adds a welcoming look to any outdoor space. PFX-3306 Lighting's fits on a 3" diameter pole (sold separately) mounting hardware is included.

LED SOURCE OPTIONS

LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L70
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty

E26 MEDIUM BASE - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L70
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty

SPECIFICATIONS

- Black or White
- Mounting Hardware Included
- Clear Prismatic Acrylic Diffuser
- Post Mount Only
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations
- Composite Construction
- Non-Corrosive

BK BLACK

WH WHITE



CALL FOR PHOTOMETRIC INFORMATION

ORDERING GUIDE

Sample Part number:PFX-3306-C-LE26-C-WH

ITEM #	DIFFUSER	LIGHT SOURCE	CCT	COLOR
PFX-3306	ACRYLIC C-Clear Prismatic	E26 MEDIUM BASE	C-4K W-3K	BK-Black WH-White
		(1) 60W MAX Medium Base LE26-9.5W 800lm (E26 LED Lamp) +		
		120V LIGHTWAVE LED		
		LR12-13W 1000lm 80CRI LT12-12W 1040lm 90CRI		

+ Lamp included.

Note : Review PFX-9213 Specification sheet for Posts and accessories details

Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.