

DC150-90

CUT-OFF LED WALLPACK LUMINAIRE

PROJECT

DATE

TYPE

NOTES



REV: 01 2021



FULL CUT-OFF, HEAVY-DUTY HOUSING

The DC150-90 is a Medium 14" Wallpack with a Die Cast Aluminum Body and Impact Resistant Glass Lens

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The DC150-90 can be Surface Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry. Additional Conduit entries Available for Photocells & other Components

120-277V STANDARD TYPE VS DISTRIBUTION

OPERATING TEMPERATURE -20C TO 40C

0C - 40C with EM Pack Option

PRODUCT APPLICATIONS

- Building Entrances
- Walkways
- Tunnels
- Loading Docks
- Bridges
- Catwalks
- Stairwells

When Specifying Options, Please Check with Factory for Availability and Lead-Time.


ORDERING GUIDE Sample Part # DC150-90 - 12W - 35K - BZ - PC1 - D1

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
DC150-90				
	12W 12 WATTS	27K 2700K - WARM WHITE	BZ BRONZE (STANDARD)	PC1 120V PHOTOCELL
	24W 24 WATTS	30K 3000K - WARM WHITE	WH WHITE	PC2 208/277V PHOTOCELL
	36W 36 WATTS	35K 3500K - NEUTRAL WHITE	BL BLACK	MS MOTION SENSOR
	48W 48 WATTS	40K 4000K - NEUTRAL WHITE	SL SILVER	MS-D2 MOTION SENSOR WITH BILEVEL DIMMING
	60W 60 WATTS	50K 5000K - COOL WHITE	CC CUSTOM COLOR	D1 0-10V DIMMING
	72W 72 WATTS	57K 5700K - DAYLIGHT		D2 STEP DIMMING (120V ONLY)
				EM EMERGENCY BATTERY PACK
				V1* 480/347V INPUT (120-277V STANDARD)
				*NOT AVAILABLE WITH EM, PHOTOCELL OR MOTION SENSOR

PRODUCT SPECIFICATIONS

NOMINAL WATTAGE	SYSTEM WATTAGE	CCT	LUMENS	EFFICACY
12W	12.65	3000K	1,530.00	120.95
12W	12.65	4000K	1,606.50	127.00
12W	12.65	5000K	1,686.83	133.35
24W	23.68	3000K	3,060.00	129.22
24W	23.68	4000K	3,213.00	135.68
24W	23.68	5000K	3,373.65	142.47
36W	34.27	3000K	4,590.00	133.94
36W	34.27	4000K	4,819.50	140.63
36W	34.27	5000K	5,060.48	147.66
48W	46.60	3000K	6,120.00	131.33
48W	46.60	4000K	6,426.00	137.90
48W	46.60	5000K	6,747.30	144.79
60W	56.83	3000K	7,650.00	134.61
60W	56.83	4000K	8,032.50	141.34
60W	56.83	5000K	8,434.13	148.41
72W	67.65	3000K	9,180.00	135.70
72W	67.65	4000K	9,639.00	142.48
72W	67.65	5000K	10,121.00	149.61

PRODUCT DIMENSIONS



POWER

POWER FACTOR >0.90 - THD <20

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.