

# PS160

WALL MOUNTED LED LUMINAIRE SHROUD



PROJECT  
NOTES

DATE

TYPE

REV: 03 2020

\* UL and FCC certification applies to the LED Luminaire only



### INTENDED USE

Provides focused illumination for outdoor use in commercial applications. Ideal for entryways, walkways, play areas, and driveways creating and inviting exterior space as well as providing safety and security. (Wall mount above 4 feet only)

### WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

### ATTRIBUTES

Rugged, weather and rust resistant housing in powder-coated finish. Available in standard Silver color for Housing and Outer Accent. Color options and combinations of Bronze, White, Black or Custom Colors are available on request.

### STANDARD

120-277V

### OPERATING TEMPERATURE

-20°C to 40°C

When Specifying Options, Please Check with Factory for Availability and Lead-Time.

## ORDERING GUIDE

Sample Part # PS160 - S - 40W - 40K - SL - SL

MODEL	LAMPS	WATTAGE	CCT	COLOR - HOUSING**	COLOR - OUTER ACCENT**
PS160	S SINGLE	25W 25 Watts	40K 4000K	SL SILVER (STANDARD)	SL SILVER (STANDARD)
		40W 40 Watts	50K 5000K	BZ BRONZE	BZ BRONZE
D DOUBLE	D DOUBLE	60W (30W UP + 30W down)		WH WHITE	WH WHITE
		80W (40W UP + 40W down)		BL BLACK	BL BLACK
				CC CUSTOM COLOR	CC CUSTOM COLOR

\*\* Check with Factory for Minimum Order Quantity (MOQ)

## PRODUCT SPECIFICATIONS

WATTAGE	CCT	DELIVERED LUMENS	EFFICACY	CRI
25W	4000K	3,325 LM	127 LM/W	>70
25W	5000K	3,280 LM	130 LM/W	>70
40W	4000K	5,238 LM	126 LM/W	>70
40W	5000K	5,131 LM	128 LM/W	>70
60W	4000K	7,809 LM	129 LM/W	>70
60W	5000K	7,854 LM	130 LM/W	>70
80W	4000K	10,598 LM	133 LM/W	>70
80W	5000K	10,598 LM	133 LM/W	>70

## DIMENSIONS (INCHES)

