

DC102

LED WALLPACK LUMINAIRE

PROJECT

DATE

TYPE

NOTES



REV: 12 2020



COMPACT, HEAVY-DUTY HOUSING

The DC102 is a Small 9" Wallpack with a Die Cast Aluminum Body and Prismatic Borosilicate Glass Lens.

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The DC102 can be Surface Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry. Additional Conduit entries Available for Photocells & other Components

120-277V STANDARD TYPE IV DISTRIBUTION

OPERATING TEMPERATURE -20C TO 40C

PRODUCT APPLICATIONS

- | | |
|--------------------|--------------------|
| Building Entrances | Bridges |
| Walkways | Catwalks |
| Tunnels | Stairwells |
| Loading Docks | Building Exteriors |

When Specifying Options, Please Check with Factory for Availability and Lead-Time.

ORDERING GUIDE


Sample Part # DC102 - 12W - 30K - BZ - PC1 - D1

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
DC102			BZ	
	12W 12 WATTS	30K 3000K - WARM WHITE	BZ BRONZE (STANDARD)	PC1 120V PHOTOCELL
	24W 24 WATTS	40K 4000K - NEUTRAL WHITE		PC2 208/277V PHOTOCELL
	36W 36 WATTS	55K 5500K - DAYLIGHT		MS MOTION SENSOR*
				D1 0-10V DIMMING
				*CONSULT FACTORY FOR ESTIMATED SHIP DATE
				QUANTITY
				1-5 Pieces (Before 11AM EST)
				5-25 Pieces
				25-100 Pieces
				SHIPS
				Same Day
				3 Days
				1 Week

PRODUCT SPECIFICATIONS

NOMINAL WATTAGE	SYSTEM WATTAGE	CCT	LUMENS	EFFICACY	DLC LISTING
12W	12.72	3000K	1,393.50	109.55	STANDARD
12W	12.72	4000K	1,463.18	115.03	STANDARD
12W	12.72	5000K	1,536.33	120.78	STANDARD
24W	23.57	3000K	2,787.00	118.24	STANDARD
24W	23.57	4000K	2,926.35	124.16	STANDARD
24W	23.57	5000K	3,072.67	130.36	STANDARD
36W	34.27	3000K	4,180.50	121.99	STANDARD
36W	34.27	4000K	4,389.53	128.09	STANDARD
36W	34.27	5000K	4,609.00	134.49	STANDARD

PRODUCT DIMENSIONS



POWER

POWER FACTOR >0.90 - THD <20

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.