

DC531 LED FLOODLIGHT LUMINAIRE

PROJECT NOTES DATE

TYPE











REV: 12 2020





COMPACT, HEAVY-DUTY HOUSING

The DC531 is a Small Floodlight Luminaire with a Die Cast Aluminum Body and Impact Resistant Glass Lens

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The DC531 comes standard with an Integral 1/2" Male Threaded Mount with an Optional Post Top Fitter available

TYPE II DISTRIBUTION 120-277V STANDARD

OPERATING TEMPERATURE -20C TO 40C

PRODUCT APPLICATIONS

Parking Lots Playgrounds

Walkways Parks & Recreational Fields

Buildings Loading Docks

Signage

When Specifying Options, Please Check with Factory for Availability and Lead-Time.

ORDERING GUIDE

DC531

MODEL WATTAGE **COLOR TEMPERATURE (CCT)**

HOUSING COLOR ΒZ

12W 12 WATTS **30K** 3000K - WARM WHITE 24W 24 WATTS 40K 4000K - NEUTRAL WHITE **36W** 36 WATTS 50K 5000K - DAYLIGHT

BZ BRONZE (STANDARD) D1 0-10V DIMMING **PT** POST TOP FITTER **OPTIONS & ACCESSORIES**


Sample Part # DC531 - 12W - 30K - BZ - D1

OUANTITY SHIPS 1-5 Pieces (Before 11AM EST) 5-25 Pieces Same Day 3 Days 1 Week

PRODUCT SPECIFICATIONS

NOMINAL WATTAGE	SYSTEM WATTAGE	CCT	LUMENS	EFFICACY	DLC LISTING
12W	12.39	3000K	1,333.00	107.59	PREMIUM
12W	12.72	4000K	1,399.65	110.04	PREMIUM
12W	12.72	5000K	1,469.63	115.54	PREMIUM
24W	23.68	3000K	2,666.00	112.58	PREMIUM
24W	23.68	4000K	2,799.30	118.21	PREMIUM
24W	23.68	5000K	2,939.26	124.12	PREMIUM
36W	34.27	3000K	3,999.00	116.69	PREMIUM
36W	34.27	4000K	4,198.95	122.53	PREMIUM
36W	34.27	5000K	4,408.90	128.65	PREMIUM

PRODUCT DIMENSIONS



25-100 Pieces



POWER

POWER FACTOR >0.90 - THD <20

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

