# Fast Flexible Focused **Lighting**

**PS160** WALL MOUNTED LED LUMINAIRE SHROUD







PROJECT

NOTES

DATE

TYPE

REV: 01 2021

<sup>\*</sup> UL and FCC certification applies to the LED Luminaire only



## **INTENDED USE**

Provides focused illumination for outdoor use in commercial applications. Ideal for entryways, walkways, play areas, and driveways creating and inviting exterior space as well as providing safety and security. (Wall mount above 4 feet only)

## **WET LOCATION, IP-65 RATED**

Engineered and Constructed for Exterior Environments

## **ATTRIBUTES**

Rugged, weather and rust resistant housing in powder-coated finish. Available in standard Silver color for Housing and Outer Accent. Color options and combinations of Bronze, White, Black or Custom Colors are available on request.

#### **ADJUSTABLE LED MODULES**

Fully adjustable LED module rotates 180 degrees to allows a range of lighting options from full cutoff, forward throw, straight up, or anything in between.

**STANDARD** 120-277V

**OPERATING TEMPERATURE** 

-20°C to 40°C

When Specifying Options, Please Check with Factory for Availability and Lead-Time.


ORDE	RING GUIE	Œ	<b>Sample Part #</b> PS160 - S - 40W - 40K - SL - SL			
MODEL	LAMPS	WATTAGE	ССТ	COLOR - HOUSING**	COLOR - OUTER ACCENT**	
PS160	0					
	<b>S</b> SINGLE BAR	<b>25W</b> 25 WATTS <b>40W</b> 40 WATTS	<b>40Κ</b> 4000Κ <b>50Κ</b> 5000Κ	SL SILVER (STANDARD) BZ BRONZE	SL SILVER (STANDARD) BZ BRONZE	
	<b>D</b> DOUBLE BAR	60W (2 X 30W BAR EACH) 80W (2 X 40W BAR EACH)	-	WH WHITE BL BLACK CC CUSTOM COLOR	WH WHITE BL BLACK CC CUSTOM COLOR	

<sup>\*\*</sup> Check with Factory for Minimum Order Quantity (MOQ)

# **PRODUCT SPECIFICATIONS**

WATTAGE	CCT	DELIVERED LUMENS	EFFICACY	CRI
25W	4000K	3,325 LM	127 LM/W	>70
25W	5000K	3,280 LM	130 LM/W	>70
40W	4000K	5,238 LM	126 LM/W	>70
40W	5000K	5,131 LM	128 LM/W	>70
60W	4000K	7,809 LM	129 LM/W	>70
60W	5000K	7,854 LM	130 LM/W	>70
80W	4000K	10,598 LM	133 LM/W	>70
80W	5000K	10,598 LM	133 LM/W	>70

#### **DIMENSIONS (INCHES)**



PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

Einfo@paraflex.com

