

PFX-3613

CP- LKFS Lumen and Kelvin
Field Selectable Canopy

ELECTRICAL DATA

Series	Measurements	Low Lumens			Mid Lumens			High Lumens		
		3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
PFX-3613 CP-10L-LKFS	Lumens	6821	6962	7228	7800	8248	8312	9297	10,506	9967
	Watts	48	43	47	57	51	57	73	69	73
	Efficacy	143	163	152	137	161	147	127	152	136
	Input Current (A)	120V = 0.40A 120V = 0.36A 120V = 0.39A	120V = 0.48A 120V = 0.43A 120V = 0.48A	120V = 0.61A 120V = 0.58A 120V = 0.61A	240V = 0.20A 240V = 0.18A 240V = 0.20A	240V = 0.24A 240V = 0.21A 240V = 0.24A	240V = 0.30A 240V = 0.29A 240V = 0.30A	277V = 0.17A 277V = 0.16A 277V = 0.17A	277V = 0.21A 277V = 0.18A 277V = 0.21A	277V = 0.26A 277V = 0.25A 277V = 0.26A

PHOTOMETRIC DATA

PFX-3613-CP-10L-LKFS Luminaire Data

Description	Canopy 10L 5K - LKFS
Total Lumens	9,993
Input Wattage	73
Efficacy (lm/W)	137
Spacing Criterion (0-180°)	1.14
Spacing Criterion (90-270°)	1.04

Zonal Lumen Summary

Zone	Lumens	%Fixt
0-20°	1,245	12.5%
0-30°	2,530	25.3%
0-40°	3,946	39.5%
20-50°	4,143	41.5%
40-70°	4,839	48.4%
0-60°	6,942	69.5%
0-80°	9,872	98.8%
0-90°	9,993	100.0%
90-180°	0	0.0%
0-180°	9,993	100.0%

