

# PFX-3103

LED MINI WALL PACK



## FEATURES

- Rectangle Slim design with less obtrusive appearance on the building while still fully
- Built-in universal Photocell.
- Die-casting Aluminum housing, Plastic lense.
- 0-10V dimming.
- 50000hrs life time.

## SUITABLE APPLICATIONS

- Warehouses
- Stadiums
- Factories Parking
- Lots Shopping
- Malls
- Supermarkets
- Logistic Centers
- Auto dealerships

## CONSTRUCTION:

Heavy die-cast aluminum alloy housing with bronze powder-coated finish.

## OPTICAL SYSTEM:

High brightness lumileds 2835 chips. high transmittance rate plastic optics.120° beam angle.

## WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

## ELECTRICAL:

Available as 120-277V input. -20°C to 45°C,

## INSTALLATION & MOUNTING:

Wall mounting with backside plate for easy install.

## CONTROLS & DIMMING

Built-in Photocell options, 0-10v dimmable

## PERFORMANCE

Model NO	PFC	Wattage Tunable	Voltage/Current Input		Light Efficiency	Kelvin Tunable
			120V	277V		
PFX-3103-26W-50K-P	>0.9	26W	0.21A	0.09A	138LM/W	3000K/4000K/5000K

**Disclaimer:**

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.



