

PFX-3121

WALL PACK



DESCRIPTION

Slim wall pack is available in two watts for a variety of applications including building perimeter, entrances, stairways and security lighting. PFX-3121 series of luminaries provides a low-profile architectural style with the power of bright, energy efficient LEDs. It has a rugged aluminum with multi-mount capabilities. 0° to +90° tilt adjustments. For a building that has a modern or futuristic look.






FEATURES

- Sealed die-casting profile for outdoor applications
- Suitable for applications requiring 3G testing prescribed by ANSI C136.31.
- Light engines are available in standard 3000K 4000 K and 5000 K configurations.
- Scalable Lumen Packages from 3,500 to 11,200 Lumens.
- Tempered UV coated flat lens provide outstanding performance, uniformity and glare control.
- Estimated 50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.
- Standard drivers feature electronic universal voltage (120-277 50/60Hz) operation.
- 1-10V Dimming


DIMENSION (INCHES)

Small size: 27W/40W

Medium size: 67W/80W



Net Weight:
27W: 3.351lb
40W: 3.968lb



Net Weight:
67W: 7.319lb
80W: 7.804lb

ORDERING GUIDE

Example: PFX-3121 40W 27V 50K Y Y Y Y

Fixture Type	Wattage	Voltage	CCT	Finish	Photocell (Option)	Dimmable	Internal Code
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
PFX-3121	27 27W	27V 120-277V	30K 3000K	D Dark Bronze	P0 With Photocell	D 1-10 Dimmable	Blank
Wall Pack Series	40 40W		40K 4000K	B Black	Blank Without Photocell		Alphanumeric
	67 67W		50K 5000K	W White			
	80 80W						

Disclaimer:
Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purpose the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

PFX-3121

WALL PACK



ELECTRICAL DATA

SYSTEM WATTS	VOLTAGE	RI	LUMENS (3000K)	LPW (3000K)	LUMENS (3500K)	LPW (3500K)	LUMENS (4000K)	LPW (4000K)	LUMENS (5000K)	LPW (5000K)
27W	120-277VAC7	0	3500lm	130 lm/W	3500lm	130 lm/W	3600lm	133 lm/W	3600lm	133 lm/W
40W	120-277VAC7	0	5100lm	128 lm/W	5100lm	128 lm/W	5300lm	133 lm/W	5300lm	133 lm/W
67W	120-277VAC7	0	9300lm	139 lm/W	9300lm	139 lm/W	9600lm	143 lm/W	9600lm	143 lm/W
80W	120-277VAC7	0	10700lm	134 lm/W	10700lm	134 lm/W	11200lm	140 lm/W	11200lm	140 lm/W

PHOTOMETRIC DATA

Number Of Drivers	Driver Current (mA)	Nominal Power (W)	INPUT VOLTAGE (V)	CURRENT (Amps)
1	430	27	120	0.23
		27	208	0.13
		27	240	0.11
		27	277	0.10
1	640	40	120	0.33
		40	208	0.19
		40	240	0.17
		40	277	0.14
1	1110	67	120	0.56
		67	208	0.32
		67	240	0.28
		67	277	0.24
1	2120	80	120	0.67
		80	208	0.38
		80	240	0.33
		80	277	0.29

Disclaimer:
Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purpose the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.