

PFX-3410

OUTDOOR BOLLARD



SPECIFICATIONS

Paraflex Lighting's PFX-3410 Bollard adds a modern look to any pathway. This fixture is available LED and its industrial strength features make it ETL listed and suitable for wet locations. PFX-3410 is designed for low mounting in reinforced concrete (by others), hardware and template is included.


FEATURES

- Powder Coated Finish
- Aluminum Housing
- Mounting Hardware Included
- Polycarbonate Lens
- Minimum Starting Temp -20°F
- ETL Listed for Wet Locations


LED SOURCE OPTIONS

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L 70
- Surge Supression
- 4000K CCT 80CRI
- 0 - 10V Dimming
- 5 Year Warranty

DIMENSION (INCHES)



Anchor Bolt M10 x 6.7"
(3 anchor bolts and template included)



ORDERING GUIDE

Sample Part PFX-3410

ITEM #	LENS	LED LIGHT SOURCE	CCT	COLOR
PFX-3410	POLYCARBONATE C-Clear	120-277V MULTI-VOLT L10-10W, 937lm	C-4K	BK-Black BZ-Bronze

Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purpose the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.