

Key Features & Benefits

- ABS Blades with Solid Finishes and Sleek Minimalist Design
- Pull Chain
- · AC Motor and ETL listed
- · Lifetime motor warranty

SOFT WHITE (3000K) BRIGHT WHITE (4000K) DAYLIGHT (5000K)

Product Specifications

Fan Size in Inches and
Mounting Type
44"/ Downrod mount only,
Angled coiling (may 18 dec

Angled ceiling (max. 18 degree) 52"/ Downrod mount only, Flat or Angled ceiling (max. 18 degree)

CFM (High) 2986

4237

Motor Type (AC, DC)/Size AC / 153x12

Indoor/Outdoor/Finish Indoor Only

Reversible, Blade Finish

Non-Reversible Available in Faux Wood (Dark Brown) and Solid Matte Black, Matte White and Silver

Damp or Wet Rated

Dry Rated

Lead Wire

54" (to allow 48-inch down-rod sold separately)

Blade Arms

N/A

AC

Remote Control (Y/N)

Ν

Light Kit (Y/N) Y (Cannot be installed without light kit)

Distance from ceiling to bottom of the light kit once installed

14.58"

Lens Type PC

Distance from Ceiling to bottom of blade once installed (inches)

9.26" Type of Bulbs No. of Blades/Blade Material 3/ABS

Bulb Wattage 18W

For LED Only

Lumen Output (Raw/Fixture) 1368/1000

Lumens/Watt 56

Color Temperature / CRI 3000K/4000K/5000K

LED Chip Brand **BRIDGELUX**

Driver Module (AC or DC)

LED Module

(can be replaced)





