

**PARAFLEX**  
Fast Flexible Focused Lighting

**24" Fan Series - 8500**

24" Fan Series - 8500 is a contemporary "fandelier", integrating a fan within the center of a powerful circular LED light ring. Available in a clean matte white finish/ brushed nickel finish. The fan is powered by a whisper-silent AC motor. A handheld remote controls the 3 speeds, and a manual switch on the fan can reverse the fan direction. Damp rated for indoor/ outdoor spaces from 300 to 450 sq ft.



**Model No.**

8501

8502

- MATTE WHITE
- BRUSHED NICKEL

**PARAFLEX**  
Fast Flexible Focused Lighting

## Specifications

Blade Sweep	13.5"
No. Blades	3
Blade Material	ABS
Down-rod (incl)	6"
Sloped Ceiling Mount	Y - up to 20 degrees
Remote Control	Y
Light Kit Included	Y
Lens Material	Opal Glass
Light Kit Wattage	24W LED
Lumen Output	1959 lm
Light Efficacy	82 LPW
Light Dimmable	Y
Light Replaceable	N
CCT	3000K Only
CRI	≥ 80
Motor Type	AC
Max Motor Wattage	50W
MAX RPM	1250
No. Speeds	3
Reversible	Y (manual switch)
Airflow (CFM)	1471 (hi) 1194 (med) 1016 (lo)
Airflow Efficiency	37 CFM/W (hi) 40 CFM/W (med) 44 CFM/W (lo)
Indoor/ Outdoor	Indoor/ Outdoor
Wet Location Rated	N
Certifications	ETL Listed for Damp Location
Limited Warranty	2 Years (Fan/ Light) Lifetime for Motor
Product Weight	21 lb
Packaged Weight	25.4 lb

## Dimensions

Fan Diameter	23.5"
Fan Height	14.75"
Fan Blade Length	5.5
Fan Blade Width	7.75"
Down-rod Length	6"
Lead Wire Length	54"
Package Size (in)	26.2 x 26.2 x 10.8



### Mounting Notes:

- Down-rod mount only to flat or sloped ceilings
- **MUST** hand minimum of 10 ft above ground
- Distance from ceiling to bottom of fan/light: 15.75"
- Distance from ceiling to bottom of fan blades: 14"
- Damp rating allows indoor/ outdoor use, fan must be protected from direct rainfall
- Can wire light separately from fan
- 54" Lead wire accommodates up to 48" down-rods (supplied by others)