

PFX-3106

CUT-OFF LED WALL PACK



FEATURES

FULL CUT-OFF, HEAVY-DUTY HOUSING

The DCST is a 14" Trapezoid Wallpack with a Die Cast Aluminum Body and Impact Resistant Glass Lens

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The DCST can be Directly Mounted over an Existing 4" Outlet Box with a 4" x 4" Gasketed Wall Plate

120-277V STANDARD TYPE V DISTRIBUTION


OPERATING TEMPERATURE -20C TO 40C

0C - 40C with EM Pack Option

PRODUCT APPLICATIONS

- Building Entrances
- Bridges
- Walkways
- Catwalks
- Tunnels
- Stairwells
- Loading Docks

DIMENSION (INCHES)



SPECIFICATIONS

NOMINAL WATTAGE	SYSTEM WATTAGE	CCT	LUMENS	EFFICACY	DLC V5.0 LISTING
12W	12.65	3000K	1,530.00	120.95	PREMIUM
12W	12.65	4000K	1,606.50	127.00	PREMIUM
12W	12.65	5000K	1,686.83	133.35	PREMIUM
24W	23.68	3000K	3,060.00	129.22	PREMIUM
24W	23.68	4000K	3,213.00	135.68	PREMIUM
24W	23.68	5000K	3,373.65	142.47	PREMIUM
36W	34.27	3000K	4,147.00	121.01	PREMIUM
36W	34.27	4000K	4,354.35	127.06	PREMIUM
36W	34.27	5000K	4,572.07	133.41	PREMIUM
48W	45.80	3000K	5,529.33	120.73	PREMIUM
48W	45.80	4000K	5,805.80	126.76	PREMIUM
48W	45.80	5000K	6,096.09	133.10	PREMIUM
60W	56.83	3000K	6,911.67	121.62	PREMIUM
60W	56.83	4000K	7,257.25	127.70	PREMIUM
60W	56.83	5000K	7,620.11	134.09	PREMIUM
72W	67.65	3000K	8,294.00	122.60	STANDARD
72W	67.65	4000K	8,708.70	128.73	STANDARD
72W	67.65	5000K	9,144.14	135.17	STANDARD

ORDERING GUIDE

Sample Part # PFX-3106 - 12W - 35K - BZ - D1

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
PFX-3106	12W 12 WATTS	27K 2700K - WARM WHITE	BZ BRONZE (STANDARD)	MS MOTION SENSOR
	24W 24 WATTS	30K 3000K - WARM WHITE	WH WHITE	MS-D2 MOTION SENSOR WITH BILEVEL DIMMING
	36W 36 WATTS	35K 3500K - NEUTRAL WHITE	BL BLACK	D1 0-10V DIMMING
	48W 48 WATTS	40K 4000K - NEUTRAL WHITE	SL SILVER	D2 STEP DIMMING (120V ONLY)
	60W 60 WATTS	50K 5000K - COOL WHITE	CC CUSTOM COLOR	EM EMERGENCY BATTERY PACK
	72W 72 WATTS	57K 5700K - DAYLIGHT		V1* 480/347V INPUT (120-277V STANDARD)
				*NOT AVAILABLE WITH EM OR MOTION SENSOR

Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purpose the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.