

# PFX-4002 Solar LED Post Top Light











## **DESCRIPTION**

The working principle of Solar LED Post Top Light: The solar panel is irradiated by sunlight, absorbs the sun light and converts it into electric energy to charge the battery. At night, the battery pack provides power to supply the LED lighting to realize the illumination.

The DC controller can ensure that the battery pack is not damaged due to overcharging or overdischarging, meanwhile, it has temperature compensation and lightning protection, reverse polarity protection and other functions such as Light control, lighting 3-5 rainy days.

Ideal for park,villa residence,Lawns,Courtyards, Roadways and many other applications.

## **FEATURES**

- · High luminous efficiency and long working life.
- · A special solar controller is used.
- · Osram light source chip is used.
- · Monocrystalline silicon solar panel.
- Excellent optics design, greatly improve the light utilization and evenness.



SPECIFICATION						
TYPE	PFX-4002-SPRCPT15W5-50K-B					
WATTAGE	15W					
ССТ	5000K					
LUMEN	1800.2 LM					
CRI	80					
MATERIAL	Die-casting aluminum					
SOLAR PANELS	5V/25W					
BATTERY	3.2V/36000mAh					
CHIP	OSRAM 3030					
LAMP SIZE	24.80 X 19.49 inch					
WORKING TIME	8H					
CHARGING TIME	3-5H					
WORKING TEMPERATURE	-4°F ~ 122°F					
CABLE	NO					
OUTDOOR RATING	IP65					
WARRANTY	2 year limited					

Note: Includes a pre-installed dusk-to-dawn light photocell sensor

#### Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.















# **PFX-4002**Solar LED Post Top Light










# **DIMENSION**



#### **PACKAGING INFORMATION**

**❖PFX-4002-SPRCPT15W5-50K-B** 

#### **OUTER BOX:**

720MMX490MMX165MM(1Pcs/CTN) 28.35" X 19.29" X 6.50"

#### **SPECIFICATIONS:**

Shell materials: Aluminum & PC

Net weight: 12.39 lbs

Finish: Black(Standard)
Product Size: 24.80" X 19.49"

(630mm X 495mm)

# **ACCESSORIES**



Screw+Hex wrench

ORDERING GUIL	PFX-4002-SPRCPT15W5-50K-Z [ D, W, B, S ]				
Model Number	Product	wattage	Voltage	ССТ	Finish
PFX-4002	SPRCPT (Solar LED Post Top Light)	15W	5V	5000K	B - Black (Standard)

#### Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.











