

# PFX-5548

LED Recessed Emergency Unit

#### STANDARD **OPTIONAL**











### **ILLUMINATION**

- · Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide upto 50-ft center-to-center spacing with a 3-ft path of egress at 12-ft mounting height.
- 1.0 watt (1 LED x 1.0 watt) per head.
- Unique all-inclusive lamp, reflector, and lens assembly.

#### **ELECTRICAL**

- Universal 120-277 voltage.
- Unique LED indicator light alerts occupant on battery condition (Red-normal, OFF-check battery).
- Charge rate/power "ON" LED indicator light and push-totest switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable nickel metal hydride battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.



## **WARRANTY / LISTING**

- Five-year warranty on all electronics and housing. Battery pro rated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations.(10°C 40°C)
- Certified to CEC under title 20 regulations.

## MOUNTING

Bar hangers included are compatible with drywall or drop ceiling mount installations.


## HOUSING

- Injection-molded, engineering 5VA flame grade, retardant, impact-resistant, thermoplastic in white or black finish.
- Injection-molded,engineering 5VA grade, flame retardant, thermoplastic oval and rectangle trim plates in white or black finish included.

#### **OPTIONS**

SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

## **DIMENSIONS**



Disclaimer

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used















# **PFX-5548** LED Recessed Emergency Unit

STANDARD











Example: PFX5548-REMW **ORDERING GUIDE** 

MODEL	HOUSING COLOR		OPTIONS	
PFX-5548-REM	W	White	SDT	Self-Diagnostics
	В	Black		

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.









info@paraflex.com