

# PFX-5607

8 Foot Vapor Tight Sensor Ready Lumen & Kelvin Selectable

## STANDARD



## HOUSING

- Light gray polycarbonate housing with stainless steel latches.

## ELECTRICAL

- Operating temperature (ambient): -40°C to 50°C (-40°F to 122°F).
- Universal 120-277V AC voltage (50-60Hz) is standard.
- 0-10VDC dimming drivers are standard.
- Input transient surge protection = 2kV.
- Power factor > 0.90.
- Total Harmonic distortion < 20%.



## OPTICAL SYSTEM

- Polycarbonate lens.
- Field selectable 3500K (warm white), 4000K (neutral white) and 5000K (cool white) color temperatures\*.
- Tri-lumen selectable delivers 9,386 to 12,716 nominal lumens\*.
- Long-life LEDs provide 174,000 hours of operation with at least 70% of initial lumen output (L70), and 53,000 hours with at least 90% of initial lumen output (L90)\*\*.
- Sensor-ready receptacle standard.
- Screw in sensor ready. Remote control required for programming (Sensor and remote control sold separately).
- LED color maintenance < -0.0005 chromaticity shift ( $\Delta u'v'$ ) over the initial 6,000 hours of operation.
- Color rendering index > 80.

\* Default kelvin temperature 4000k and highest lumen output.

\*\*L70 & L90 hours are IES TM-21-11 calculated hours.

## MOUNTING

- Surface mount kit is standard and v-hooks included. (Chain supplied by others.)
- Optional cable mount kit provides luminaire suspension.
- Easy installation in new construction or retrofit applications.

## CODE COMPLIANCE

- cULus listed for wet locations.
- DLC standard listed.
- Complies with FCC part 15, class A.
- IP66 rated for ingress protection.
- IK10 rated for impact protection.

## WARRANTY / LISTING

- 5 year warranty on all electronics and housing.



Model #	L (in)	W (in)	H (in)	Weight (lbs)
PFX-5607 VTSR-8FT-12109L-3CCT	94.49	3.74	3.11	10.5

## ORDERING GUIDE

Example: PFX-5607-8FT-12109L-3CCT

Model	Nominal Lumen Output (Selectable)		Kelvin Selectable
PFX-5607-VTSR-8FT	12109L	12,000 / 10,000 / 9,000 lm	3CCT 3500K / 4000K / 5000K

### Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

# PFX-5607

8 Foot Vapor Tight Sensor Ready Lumen & Kelvin Selectable

STANDARD



## ACCESSORIES (ORDER SEPARATELY)

### Sensor

HD09VR-PH5-1-90\*  
HD09VR-MH5-1 -90\*  
HD05R

- = Passive infrared sensor with 90° elbow adapter- maximum mounting height = 39FT.
- = Microwave step-dimming sensor with 90° elbow adapter - maximum mounting height = 49FT.
- = Remote control for HD09VR sensors.

\*HD09VR series has 5-dial setting capability.

Factory settings for Sensor : detection area =100%, hold time = 5 sec, stand-by period = 0 sec, stand-by dimming level = 10%, daylight threshold = disabled

### Photocell

HD07VR-A-1-90

- = 12VDC photocell with 90°elbow adapter; RCA jack, factory set to turn on at 10 lux, turns off at 100 lux

### Mounting Option

CMK3  
CMK5

- = 3 Meter cable mount kit
- = 5 Meter cable mount kit

## COMPATIBLE DIMMERS AND CONTROLS

Manufacturer	Model Number	Dimmer Range	Load Switching Capacity
Leviton	IP710-LFZ	10%-100%	1200W
Lutron	DVSTV	10%-100%	450W

## ELECTRICAL DATA

Series	CCT	Input Amps (A)									
		Low Lumens			Mid Lumens			High Lumens			
		120V	240V	277V	120V	240V	277V	120V	240V	277V	
PFX-5607-VTSR 8FT-12109L-3CCT	3500K	0.57	0.29	0.25	0.66	0.33	0.27	0.77	0.39	0.33	
	4000K	0.55	0.28	0.24	0.63	0.32	0.27	0.75	0.38	0.33	
	5000K	0.58	0.29	0.25	0.66	0.33	0.29	0.79	0.40	0.34	

### Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

# PFX-5607

8 Foot Vapor Tight Sensor Ready Lumen & Kelvin Selectable

STANDARD



## LUMEN TABLES

Series	Measurements	Low Lumens			Mid Lumens			High Lumens		
		3500K	4000K	5000K	3500K	4000K	5000K	3500K	4000K	5000K
PFX-5607-VTSR 8FT-12109L-3CCT	Lumens	9,386	9,596	9,280	10,574	10,837	10,469	12,340	12,716	12,223
	Watt	68.68	66.38	69.03	78.64	75.8	79.13	92.4	90.4	94.94
	Efficacy	136.67	144.56	134.43	134.46	142.97	132.30	133.55	140.66	128.74

**Disclaimer:**

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.