

Key Features & Benefits

- Outdoor rated ABS Blades with Faux Wood Finishes
- DC Motor and ETL listed
- Lifetime motor warranty



SOFT WHITE (3000K) BRIGHT WHITE (4000K) DAYLIGHT (5000K)

Adjust color of light with included remote control

Product Specifications

i i o di di ci o p e ci i i cationo						
Fan Size in Inches	CFM (High)	-	Motor Type (AC, DC)/Siz	e e	Indoor/Outdoor/Finish Indoor / Outdoor	
52"/ Downrod mount only, Flat or	6411 6837 Blade Arms		DC / 156x8	•	Damp or Wet . Wet-rated outdoor ceiling fans are designed to withstand direct contact with water and moisture, which makes them ideal for open gazebos and pergolas 	
Angled ceiling (max. 18 degree) 60"/ Downrod mount only, Flat or Angled ceiling (max. 18 degree)			DC / 156x12	moisture, wł		
Reversible, Blade Finish			Damp or Wet Rated	Lead Wire		
Non-Reversible Available in Faux Wood	N/A		Wet		54" (to allow 48" downrod (sold separately))	
Remote Control (Y/N) Y Light Kit (Y/N) Y / (Can be installed with or	Distance from ceiling to bottom of the light kit (or lowest part of fan) once installed: 13.8"		Distance from Ceiling to bottom of blade once installed : 12.68 "	No. of Blade: 3/ABS	No. of Blades/Blade Material 3/ABS	
without Light kit) Light kit cover included	Lens Type		Bulb Wattage	Type of Bulb	Type of Bulbs	
For LED Only	PC		18W (Dimmable)	LED Module	(can be replaced)	
Lumen Output (Raw/Fixture) 1449/800			nperature / CRI	LED Chip Brand	Driver Module (AC or DC)	
1449/000			00K/5000K /≥90	BRIDGELUX	AC	

PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

A 3 Luger Rd. #1 - Denville, NJ 07831

E info@paraflex.com

W www.paraflex.com

P 973-340-6040

Fast Flexible Focused Lighting