

PFX-5311

Undercabinet Light Selectable CCT

STANDARDS



HOUSING

- Aluminum, white housing.

ELECTRICAL

- Operating temperature (ambient): -20°C to 45°C (-4°F to 113°F).
- Universal 120V AC voltage (60Hz) is standard.
- PFX-5311-9-3L-5CCT = 4W
- PFX-5311-12-8L-5CCT = 8W
- PFX-5311-18-12L-5CCT = 12W
- PFX-5311-24-16L-5CCT = 16W
- PFX-5311-36-23L-5CCT = 24W
- Two or more lights can be linked.(see page 2 for run limitations)
- Maximum Load: Maximum limit of 2A per linking circuit.
- Triac dimming.
- Input transient surge protection = 1kV.
- Power factor > 0.90.
- Total Harmonic distortion < 20%.

OPTICAL SYSTEM

- Polycarbonate diffuser.
- Rotatable light bar swivel 65°.
- Field selectable 2700k(soft white), 3000k(warm white), 3500k(warm/neutral white), 4000k (neutral white) and 5000k (cool white) color temperatures*.
- Delivers a range of 300 to 2,300 nominal lumens*.
- Long-life LEDs provide 167,000 hours of operation with at least 70% of initial lumen output (L70), and 51,000 hours with at least 90% of initial lumen output (L90)**.
- LED color maintenance < 0.0059 chromaticity shift ($\Delta u'v'$) over the initial 6,000 hours of operation.
- Integrated PIR sensor is standard.
- Color rendering index > 90.

* Factory Default kelvin temperature 4000k.

**L70 hours are IES TM-21-11 calculated hours.



MOUNTING


- Surface mounting.

CODE

- cETLus listed for damp locations.
- Complies with FCC part 15, class B.
- Complies with Title 24.

WARRANTY / LISTING

- 5 year warranty on all electronics and housing.



Model #	L (in)	W (in)	H (in)	Weight (lbs)
PFX-5311-9-3L-5CCT	8.98	3.35	1.51	1.06
PFX-5311-12-8L-5CCT	11.97	3.35	1.51	1.19
PFX-5311-18-12L-5CCT	17.99	3.35	1.51	1.33
PFX-5311-24-16L-5CCT	23.98	3.35	1.51	1.50
PFX-5311-36-23L-5CCT	36.02	3.35	1.51	1.61

ORDERING GUIDE

Example: PFX-5311-9-3L-5CCT

Model	Nominal Lumen Output		Kelvin Selectable
PFX-5311-9	3L	300 lm	
PFX-5311-12	8L	800 lm	
PFX-5311-18	12L	1200 lm	
PFX-5311-24	16L	1600 lm	
PFX-5311-36	23L	2300 lm	

5CCT 2700 / 3000 / 3500 / 4000 / 5000K

Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

PFX-5311

Undercabinet Light Selectable CCT

STANDARDS



ACCESSORIES (ORDER SEPARATELY)

Linking Connector

- ZZ-CORDPLUG-UC-4C3P = 120V,4FT white cord with NEMA 5-15 Plug
- ZZ-UC-CONNECT-2IN = 2 inch Linking Connector Cable
- ZZ-UC-CONNECT-2.5IN = 2.5 inch Linking Connector Cable
- ZZ-UC-CONNECT-3IN = 3 inch Linking Connector Cable
- ZZ-UC-CONNECT-24IN = 24 inch Linking Connector Cable

COMPATIBLE DIMMERS AND CONTROLS

Manufacturer	Model Number		
Lutron	TG-600PR-WH	CTCL-153PDH-WH	TGCL-153PH-LA
	SLV-600P-AL	DVCL-153P	MSCL-OP153M
	PD-6WCL	CT-103PR-WH	DVWCL-153PH
	RCL-153RNL	-	-
Leviton	6672	RNL06	-

MAXIMUM RUN

Series	Max. Quantity	Max. Size
PFX-5311-9-3L-5CCT	120 Units	90-ft
PFX-5311-12-8L-5CCT	60 Units	60-ft
PFX-5311-18-12L-5CCT	40 Units	60-ft
PFX-5311-24-16L-5CCT	30 Units	60-ft
PFX-5311-36-23L-5CCT	20 Units	60-ft

NOTE: Maximum limit of 2A per linking circuit.

Disclaimer:

Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

PFX-5311

Undercabinet Light Selectable CCT

STANDARDS



LUMEN TABLES

Series	Measurements	Lumens				
		2700K	3000K	3500K	4000K	5000K
PFX-5311-9-3L-5CCT	Lumens	307	326	339	344	340
	Watts	4.02	4	3.95	3.98	4.01
	Efficacy	76.37	81.50	85.82	86.43	84.79

Series	Measurements	Lumens				
		2700K	3000K	3500K	4000K	5000K
PFX-5311-12-8L-5CCT	Lumens	677	714	752	764	751
	Watts	7.96	7.86	7.71	7.84	7.98
	Efficacy	85.05	90.84	97.54	97.45	94.11

Series	Measurements	Lumens				
		2700K	3000K	3500K	4000K	5000K
PFX-5311-18-12L-5CCT	Lumens	1,019	1,082	1,138	1,152	1,136
	Watts	11.95	11.77	11.49	11.68	11.94
	Efficacy	85.27	91.93	99.04	98.63	95.14

Series	Measurements	Lumens				
		2700K	3000K	3500K	4000K	5000K
PFX-5311-24-16L-5CCT	Lumens	1,453	1,544	1,612	1,638	1,614
	Watts	15.94	15.63	15.31	15.53	15.9
	Efficacy	91.15	98.78	105.29	105.47	101.51

Series	Measurements	Lumens				
		2700K	3000K	3500K	4000K	5000K
PFX-5311-36-23L-5CCT	Lumens	2,096	2,202	2,298	2,338	2,322
	Watts	23.65	22.98	22.54	22.92	23.64
	Efficacy	88.63	95.82	101.95	102.01	98.22

Disclaimer:
Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

PFX-5311

Undercabinet Light Selectable CCT

STANDARDS



ELECTRICAL DATA

Series	CCT	Input Amps (A)	
		Lumens	
		120V	
PFX-5311-9-3L-5CCT	2700K	0.03	
	3000K	0.03	
	3500K	0.03	
	4000K	0.03	
	5000K	0.03	

Series	CCT	Input Amps (A)	
		Lumens	
		120V	
PFX-5311-12-8L-5CCT	2700K	0.07	
	3000K	0.07	
	3500K	0.06	
	4000K	0.07	
	5000K	0.07	

Series	CCT	Input Amps (A)	
		Lumens	
		120V	
PFX-5311-18-12L-5CCT	2700K	0.10	
	3000K	0.10	
	3500K	0.10	
	4000K	0.10	
	5000K	0.10	

Series	CCT	Input Amps (A)	
		Lumens	
		120V	
PFX-5311-24-16L-5CCT	2700K	0.13	
	3000K	0.13	
	3500K	0.13	
	4000K	0.13	
	5000K	0.13	

Series	CCT	Input Amps (A)	
		Lumens	
		120V	
PFX-5311-36-23L-5CCT	2700K	0.20	
	3000K	0.19	
	3500K	0.19	
	4000K	0.19	
	5000K	0.20	

Disclaimer:
Due to the rapid pace of technology change in the Lighting industry, the Information and Data presented in this spec sheet is for reference purposes only, please confirm with PARAFLEX at the time of finalizing the order or design. PARAFLEX does not warrant or represent that the information is free from errors or omission. The information may change without notice and PARAFLEX is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.