

DC102

LED WALLPACK LUMINAIRE



PROJECT

DATE

TYPE

NOTES

REV: 17 0903



COMPACT, HEAVY-DUTY HOUSING

The DC102 is a Small 9" Wallpack with a Die Cast Aluminum Body and Prismatic Borosilicate Glass Lens.

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The DC102 can be Surface Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry. Additional Conduit entries Available for Photocells & other Components

120-277V STANDARD

PRODUCT APPLICATIONS

- | | |
|--------------------|--------------------|
| Building Entrances | Bridges |
| Walkways | Catwalks |
| Tunnels | Stairwells |
| Loading Docks | Building Exteriors |

ORDERING GUIDE

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
DC102	14W	27K 2700K - WARM WHITE	BZ BRONZE (STANDARD)	PC1 120V PHOTOCELL
	28W	30K 3000K - WARM WHITE	WH WHITE	PC2 208/277V PHOTOCELL
	42W	35K 3500K - NEUTRAL WHITE	BL BLACK	MS MOTION SENSOR
		40K 4000K - NEUTRAL WHITE	SL SILVER	D1 0-10V DIMMING
		50K 5000K - COOL WHITE	CC CUSTOM COLOR	D2 STEP DIMMING
		55K 5500K - DAYLIGHT		V1* 480/347V INPUT (120-277V STANDARD)

*NOT AVAILABLE WITH A PHOTOCELL OR MOTION SENSOR

PRODUCT SPECIFICATIONS

WATTAGE	SYSTEM W	DELIVERED LUMENS	EFFICACY	CRI
14W	12W	1,645 LM	132 LM/W	>85
28W	24W	3,015 LM	128 LM/W	>85
42W	35W	4,595 LM	133 LM/W	>85

PRODUCT DIMENSIONS

