

# DC560

LED FLOODLIGHT LUMINAIRE

PROJECT

DATE

TYPE

NOTES



REV: 17 0903



### COMPACT, HEAVY-DUTY HOUSING

The DC560 is a 12"x 8" Floodlight Luminaire with a Die Cast Aluminum Body and Impact Resistant Glass Lens

### WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

### EASY TO INSTALL MOUNTING

The DC560 comes standard with an Integral 1/2" Female Threaded Mount

### 120-277V STANDARD

### PRODUCT APPLICATIONS

- Parking Lots
- Walkways
- Buildings
- Signage
- Playgrounds
- Parks & Recreational Fields
- Loading Docks

## ORDERING GUIDE

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
DC560	14W	27K 2700K - WARM WHITE	BZ BRONZE (STANDARD)	PC1 120V PHOTOCELL
	28W	30K 3000K - WARM WHITE	WH WHITE	PC2 208/277V PHOTOCELL
	42W	35K 3500K - NEUTRAL WHITE	BL BLACK	D1 0-10V DIMMING
	56W	40K 4000K - NEUTRAL WHITE	SL SILVER	D2 STEP DIMMING
		50K 5000K - COOL WHITE	CC CUSTOM COLOR	V1* 480/347V INPUT (120-277V STANDARD)
		55K 5500K - DAYLIGHT		*NOT AVAILABLE WITH A PHOTOCELL OR MOTION SENSOR

## PRODUCT SPECIFICATIONS

WATTAGE	SYSTEM W	DELIVERED LUMENS	EFFICACY	CRI	EPA
14W	12W	1,645 LM	132 LM/W	>85	
28W	24W	3,015 LM	128 LM/W	>85	
42W	35W	4,595 LM	133 LM/W	>85	
56W	48W	6,250 LM	130 LM/W	>85	

### PRODUCT DIMENSIONS

