

DC400

LED FLOODLIGHT LUMINAIRE

PROJECT

DATE

TYPE

NOTES



REV: 17 0903



COMPACT, HEAVY-DUTY HOUSING

The DC400 is a 16"x 10" Floodlight Luminaire with a Die Cast Aluminum Body and Impact Resistant Glass Lens

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

VERSATILE MOUNTING OPTIONS

The DC400 is available with Three Mounting Options: Trunnion, Slip-Fitter and Straight Arm

120-277V STANDARD

PRODUCT APPLICATIONS

- Parking Lots
- Walkways
- Buildings
- Signage
- Playgrounds
- Parks & Recreational Fields
- Loading Docks

ORDERING GUIDE

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	MOUNTING	OPTIONS & ACCESSORIES
DC400	14W	27K 2700K - WARM WHITE	BZ BRONZE (STANDARD)	NA NONE (BY OTHERS)	PC1 120V PHOTOCELL
	28W	30K 3000K - WARM WHITE	WH WHITE	TR TRUNNION MOUNT	PC2 208/277V PHOTOCELL
	42W	35K 3500K - NEUTRAL WHITE	BL BLACK	SF SLIP-FITTER	MS MOTION SENSOR
	56W	40K 4000K - NEUTRAL WHITE	SL SILVER	ST STRAIGHT ARM	D1 0-10V DIMMING
	70W	50K 5000K - COOL WHITE	CC CUSTOM COLOR		D2 STEP DIMMING
	84W	55K 5500K - DAYLIGHT			EM EMERGENCY BATTERY PACK
					V1* 480/347V INPUT (120-277V STANDARD)

*NOT AVAILABLE WITH A PHOTOCELL OR MOTION SENSOR

PRODUCT SPECIFICATIONS

WATTAGE	SYSTEM W	DELIVERED LUMENS	EFFICACY	CRI	EPA
14W	12W	1,645 LM	132 LM/W	>85	
28W	24W	3,015 LM	128 LM/W	>85	
42W	35W	4,595 LM	133 LM/W	>85	
56W	48W	6,250 LM	130 LM/W	>85	
70W	59W	7,610 LM	129 LM/W	>85	
84W	71W	9,190 LM	129 LM/W	>85	

PRODUCT DIMENSIONS

