

# DC150

LED WALLPACK LUMINAIRE

PROJECT

DATE

TYPE

NOTES



REV: 17 0903



### HEAVY-DUTY HOUSING

The DC150 is a Medium 14" Wallpack with a Die Cast Aluminum Body and Prismatic Borosilicate Glass Lens.

### WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

### EASY TO INSTALL MOUNTING

The DC150 can be Surface Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry. Additional Conduit entries Available for Photocells & other Components

### 120-277V STANDARD

### PRODUCT APPLICATIONS

- Building Entrances
- Walkways
- Tunnels
- Loading Docks
- Bridges
- Catwalks
- Stairwells

## ORDERING GUIDE

| MODEL | WATTAGE | COLOR TEMPERATURE (CCT)   | HOUSING COLOR        | OPTIONS & ACCESSORIES                  |
|-------|---------|---------------------------|----------------------|--|
| DC150 | 14W     | 27K 2700K - WARM WHITE    | BZ BRONZE (STANDARD) | PC1 120V PHOTOCELL                     |
|       | 28W     | 30K 3000K - WARM WHITE    | WH WHITE             | PC2 208/277V PHOTOCELL                 |
|       | 42W     | 35K 3500K - NEUTRAL WHITE | BL BLACK             | MS MOTION SENSOR                       |
|       | 56W     | 40K 4000K - NEUTRAL WHITE | SL SILVER            | D1 0-10V DIMMING                       |
|       |         | 50K 5000K - COOL WHITE    | CC CUSTOM COLOR      | D2 STEP DIMMING                        |
|       |         | 55K 5500K - DAYLIGHT      |                      | EM EMERGENCY BATTERY PACK              |
|       |         |                           |                      | V1* 480/347V INPUT (120-277V STANDARD) |

\*NOT AVAILABLE WITH A PHOTOCELL OR MOTION SENSOR

## PRODUCT SPECIFICATIONS

| WATTAGE | SYSTEM W | DELIVERED LUMENS | EFFICACY | CRI |
|---------|----------|------------------|----------|-----|
| 14W     | 12W      | 1,645 LM         | 132 LM/W | >85 |
| 28W     | 24W      | 3,015 LM         | 128 LM/W | >85 |
| 42W     | 35W      | 4,595 LM         | 133 LM/W | >85 |
| 56W     | 48W      | 6,250 LM         | 130 LM/W | >85 |

## PRODUCT DIMENSIONS

