

# DCSHM-UD

ROUND UP/DOWN LED WALLPACK LUMINAIRE

PROJECT

DATE

TYPE

NOTES



REV: 17 0903



### UPLIGHT/DOWNLIGHT, HEAVY-DUTY HOUSING

The DCSHM is an 18" Half-Moon Wallpack with a Die Cast Aluminum Body and Impact Resistant Glass Lens That Provides a Variety of Uplight and Downlight Options

### WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

### EASY TO INSTALL MOUNTING

4" x 4" Gasketed Wall Plate allows the Installer to Quickly Mount and Wire the Fixture without Opening the Housing

### 120-277V STANDARD

### PRODUCT APPLICATIONS

- Building Entrances
- Walkways
- Tunnels
- Loading Docks
- Bridges
- Catwalks
- Stairwells

## ORDERING GUIDE

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
DCSHM	14W (UP ONLY)	27K 2700K - WARM WHITE	BZ BRONZE (STANDARD)	MS MOTION SENSOR
	28W (UP/DN)	30K 3000K - WARM WHITE	WH WHITE	D1 0-10V DIMMING
	42W (UP/DN)	35K 3500K - NEUTRAL WHITE	BL BLACK	D2 STEP DIMMING
	56W (UP/DN)	40K 4000K - NEUTRAL WHITE	SL SILVER	EM EMERGENCY BATTERY PACK
		50K 5000K - COOL WHITE	CC CUSTOM COLOR	V1* 480/347V INPUT (120-277V STANDARD)
		55K 5500K - DAYLIGHT		*NOT AVAILABLE WITH A PHOTOCELL OR MOTION SENSOR

## PRODUCT SPECIFICATIONS

WATTAGE	SYSTEM W	UPLIGHT LM	DOWNLIGHT LM	EFFICACY	CRI
14W	12W	1,645 LM	0 LM	132 LM/W	>85
28W	24W	1,645 LM	1,645 LM	128 LM/W	>85
42W	35W	1,645 LM	3,015 LM	133 LM/W	>85
56W	48W	1,645 LM	4,595 LM	130 LM/W	>85

### PRODUCT DIMENSIONS

