

ZFL-52

COMPACT LED FLOODLIGHT LUMINAIRE



PROJECT

DATE

TYPE

NOTES

REV: 17 1002



HEAVY-DUTY, IP-66 RATED HOUSING

The ZFL is constructed with a Die Cast Aluminum Body and Heat and Impact Resistant Glass to create a Heavy-Duty Housing

WET LOCATION RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING HARDWARE

The ZFL comes standard with a 160° Swivel Bracket engineered to be installed within a variety of Exterior Applications

120-277V STANDARD

PRODUCT APPLICATIONS

- Building Entrances
- Walkways
- Tunnels
- Loading Docks
- Canopies
- Bridges
- Catwalks
- Stairwells
- Building Facades

ORDERING GUIDE

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	OPTICS
ZFL	52W	50K	
	52W	50K 5000K - COOL WHITE	WB WIDE (80°) BEAM

PRODUCT SPECIFICATIONS

WATTAGE	SYSTEM W	DELIVERED LUMENS	EFFICACY	CRI	EPA
57W	52W	4,335 LM	75 LM/W	>65	

ZFL-52 PRODUCT DIMENSIONS

