

ZSLM

LOW-PROFILE LED WALLPACK LUMINAIRE



PROJECT

DATE

TYPE

NOTES

REV: 17 1002



LOW PROFILE, IP-65 RATED HOUSING

The Compact Housing is constructed with a Die Cast Aluminum Body and Heat and Impact Resistant Glass

WET LOCATION RATED

Engineered and Constructed for Exterior Environments

ADJUSTABLE BEAM ANGLE

The ZSLM provides a Customizable Beam that adjusts from Full Cut-Off to 65° to provide the right angle of light for your project

120-277V STANDARD

PRODUCT APPLICATIONS

- Building Entrances
- Walkways
- Tunnels
- Loading Docks
- Bridges
- Catwalks
- Stairwells

ORDERING GUIDE

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	OPTIONS & ACCESSORIES
ZSLM			
	12W	30K 3000K - WARM WHITE	PC1 120V PHOTOCELL
	28W	40K 4100K - NEUTRAL WHITE	PC2 208/277V PHOTOCELL
	49W	50K 5000K - COOL WHITE	
	80W		
	124W		

PRODUCT SPECIFICATIONS

SYSTEM WATTS	CTT	DELIVERED LUMENS	EFFICACY	CRI	12W PRODUCT DIMENSIONS	28-49W PRODUCT DIMENSIONS
12W	3000K	1,211 LM	101 LM/W	>80		
12W	4000K	1,285 LM	107 LM/W	>80		
12W	5000K	1,321 LM	110 LM/W	>80		
28W	3000K	3,099 LM	111 LM/W	>80		
28W	4000K	3,239 LM	116 LM/W	>80		
28W	5000K	3,298 LM	118 LM/W	>80		
49W	3000K	4,920 LM	100 LM/W	>80		
49W	4000K	5,193 LM	106 LM/W	>80		
49W	5000K	5,287 LM	108 LM/W	>80		
80W	3000K	8,821 LM	110 LM/W	>80		
80W	4000K	9,056 LM	113 LM/W	>80		
80W	5000K	9,241 LM	116 LM/W	>80		
124W	3000K	13,106 LM	106 LM/W	>80		
124W	4000K	13,796 LM	111 LM/W	>80		
124W	5000K	14,227 LM	115 LM/W	>80		